

View Online at <https://aerobasegroup.com/nsn/5340-01-388-4455>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.800 inches

**Second Leg Length:**

0.800 inches

**Second Leg Width:**

0.800 inches

**First Leg Hole Diameter:**

Between 0.166 inches and 0.169 inches

**Second Leg Hole Diameter:**

Between 0.168 inches and 0.174 inches

**Second Leg Distance Between Hole Centers Along Length:**

3.125 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.532 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.188 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**Center Section Height:**

2.440 inches

**Center Section Width:**

3.500 inches

**Center Section Thickness:**

0.063 inches

**First Leg Width:**

2.800 inches

**First Leg Distance Between Hole Centers Along Length:**

2.188 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.400 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.306 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

0.12 radians

**Second Leg Angle:**

0.12 radians

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil--c-5541, cl3 military specification single treatment response

**Style Designator:**

Adjacent angles

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

spec.