

View Online at <https://aerobasegroup.com/nsn/5340-01-389-3795>

Cross Sectional Shape:

Flat

Hole Diameter:

Between 0.125 inches and 0.131 inches

Width:

8.430 inches

Edge Shape:

Rectangle, multi holes

Length:

10.230 inches

Hole Quantity Along Length:

8

Hole Quantity Along Width:

10

Distance Between Holes Along Length:

1.150 inches and 2.350 inches and 1.605 inches and 2.395 inches

Distance Between Holes Along Width:

8.080 inches and 2.020 inches

Distance From First Hole Centerline To End Along Length:

0.175 inches

Distance From First Hole Centerline To End Along Width:

0.175 inches

Body Thickness:

Between 0.025 inches and 0.035 inches

Securing Device Type:

Threaded fastener

Mounting Opening Shape Style:

Unthreaded hole

End Application:

Pacer dawn

Special Features:

Mtg holes csk 0.240 by 100.00 degrees pom 1.000 deg; item requires 18 modified screws, p/n/ 801278- (make from nas514p440-8p) & 18 o-rings, p/n m25998/1-003

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 type t6 federal specification single material response

Surface Treatment:

Chromate and primer and paint polyurethane

Surface Treatment Specification:

Mil-c-5541 cl 3 military specification 1st treatment response and mil-f-14072 military specification 2nd treatment response and mil-c-83286 military specification 3rd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531c0

Mil-std (military Standard):

Mil-c-5541 spec.