NSN 5340-01-389-7004

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-389-7004

Mounting Hole Type:

Plain

First Leg Length:

Between 37.0 millimeters and 39.0 millimeters

Second Leg Length:

Between 37.0 millimeters and 39.0 millimeters

Second Leg Width:

19.05 millimeters

Second Leg Corner Radius:

Between 5.35 millimeters and 7.35 millimeters

First Leg Hole Diameter:

Between 9.5 millimeters and 10.5 millimeters

Second Leg Hole Diameter:

Between 6.5 millimeters and 7.5 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

Between 13.0 millimeters and 17.0 millimeters

First Leg Thickness:

4.7625 millimeters

Second Leg Thickness:

4.7625 millimeters

Center Section Height:

Between 55.0 millimeters and 57.0 millimeters

Center Section Width:

19.05 millimeters

Center Section Thickness:

4.7625 millimeters

First Leg Width:

19.05 millimeters

First Leg Corner Radius:

Between 5.35 millimeters and 7.35 millimeters

First Leg Distance From Edge To Hole Center Along Length:

Between 13.0 millimeters and 17.0 millimeters

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

NSN 5340-01-389-7004

Double Angle Bracket - Page 2 of 2

Fiig: A042a0



First Leg Angle:
Between 3.0 radians and 5.0 radians
Second Leg Angle:
Between 3.0 radians and 5.0 radians
Material:
Steel or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel uns k02500
Material Specification:
Astm a36 assn standard single material response or astm 570 assn standard single material response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No.