

View Online at <https://aerobasegroup.com/nsn/5340-01-390-2469>

Cross Sectional Shape:

Flat

Hole Diameter:

0.128 inches

Width:

6.570 inches

Length:

10.545 inches

Corner Radius:

0.220 inches

Hole Quantity Along Length:

9

Hole Quantity Along Width:

6

Distance Between Holes Along Length:

1.600 inches and 1.835 inches and 2.400 inches and 5.700 inches

Distance Between Holes Along Width:

2.600 inches and 3.350 inches and 2.000 inches

Distance Between Hole Centerline And First Hole Along Width:

0.260 inches

Distance From First Hole Centerline To End Along Length:

0.270 inches

Body Thickness:

0.150 inches

Securing Device Type:

Special

Mounting Opening Shape Style:

Unthreaded hole

End Application:

Pacer dawn

Features Provided:

Special marking

Special Features:

Original name cover, power amplifier; item is 'I' shaped w/mtg holes cbored opp side 0.266 in. Diameter to 0.06 remaining thk; 3 holes breakout permissible, diameter 0.250 in. To 0.090 remaining thk; cover must be capable of withstanding 30 lbs psi differential pressure; cast tol pom 0.008 in. Up to & including 4 in., and pom 0.0015 for each additional inch

Material:

Aluminum alloy 360.0 or aluminum alloy 380.0

Material Specification:

Qq-a-591 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 cl 3 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531c0

Mil-std (military Standard):

Mil-c-5541 spec.