

View Online at <https://aerobasegroup.com/nsn/5340-01-390-2469>

**Cross Sectional Shape:**

Flat

**Hole Diameter:**

0.128 inches

**Width:**

6.570 inches

**Length:**

10.545 inches

**Corner Radius:**

0.220 inches

**Hole Quantity Along Length:**

9

**Hole Quantity Along Width:**

6

**Distance Between Holes Along Length:**

1.600 inches and 1.835 inches and 2.400 inches and 5.700 inches

**Distance Between Holes Along Width:**

2.600 inches and 3.350 inches and 2.000 inches

**Distance Between Hole Centerline And First Hole Along Width:**

0.260 inches

**Distance From First Hole Centerline To End Along Length:**

0.270 inches

**Body Thickness:**

0.150 inches

**Securing Device Type:**

Special

**Mounting Opening Shape Style:**

Unthreaded hole

**End Application:**

Pacer dawn

**Features Provided:**

Special marking

**Special Features:**

Original name cover, power amplifier; item is 'I' shaped w/mtg holes cbored opp side 0.266 in. Diameter to 0.06 remaining thk; 3 holes breakout permissible, diameter 0.250 in. To 0.090 remaining thk; cover must be capable of withstanding 30 lbs psi differential pressure; cast tol pom 0.008 in. Up to & including 4 in., and pom 0.0015 for each additional inch

**Material:**

Aluminum alloy 360.0 or aluminum alloy 380.0

**Material Specification:**

Qq-a-591 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541 cl 3 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A531c0

**Mil-std (military Standard):**

Mil-c-5541 spec.