
# NSN 5340-01-390-4199

Double Angle Bracket - Page 1 of 2





Mounting Hole Type:	
Plain	
First Leg Length:	
0.750 inches	
Second Leg Length:	
0.750 inches	
First Leg Hole Diameter:	
Between 0.385 inches and 0.392 inches	
First Leg Thickness:	
0.090 inches	
Second Leg Thickness:	
0.090 inches	
Center Section Height:	
1.570 inches	
Center Section Width:	
0.870 inches	
Center Section Thickness:	
0.090 inches	
First Leg Width:	
0.870 inches	
First Leg End Width:	
0.670 inches	
First Leg Distance From Edge To Hole Center Along Width:	
0.438 inches	
First Leg Distance From Edge To Hole Center Along Length:	
0.375 inches	
First Leg Style:	
Chamfered ends	
First Leg Hole Arrangement Style:	
One hole	
Second Leg Relationship To First Leg:	
Identical	
First Leg Angle:	
90.0 degrees	
Second Leg Angle:	
90.0 degrees	
First Leg Chamfer Angle:	
45.0 degrees	
Material:	
Aluminum alloy 5052	
Material Specification:	
Og a 250/8 h24 fadaral anapification single material response	

Qq-a-250/8 h34 federal specification single material response

## NSN 5340-01-390-4199

Double Angle Bracket - Page 2 of 2



Surface Treatment:

Plastic polyurethane

#### Surface Treatment Specification:

Mil-c-46168 type 1, 2, or 3 military specification single treatment response

#### Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

### Fiig:

A042a0

#### Mil-std (military Standard):

Mil-c-46168 spec.