

View Online at <https://aerobasegroup.com/nsn/5340-01-393-4207>

First Leg Length:

0.4400 inches

Second Leg Length:

0.5000 inches

Second Leg Width:

0.4300 inches

First Leg Slot Length:

0.3200 inches

First Leg Slot Width:

0.1090 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.1900 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.1900 inches

Second Leg Slot Width:

0.2030 inches

First Leg Thickness:

0.0600 inches

Second Leg Thickness:

0.0600 inches

First Leg Width:

0.4300 inches

First Leg End Width:

0.4300 inches

First Leg Distance From Edge To Hole Center Along Width:

0.1900 inches

First Leg Distance From Edge To Hole Center Along Length:

0.0600 inches

Second Leg Side Radius:

0.2030 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Side radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Material:

Aluminum alloy 6063

Material Specification:

Qq-a-200/9 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, cl 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.