

View Online at <https://aerobasegroup.com/nsn/5340-01-394-0424>

Mounting Hole Type:

Plain

First Leg Length:

5.7500 inches

Second Leg Length:

4.9200 inches

Reinforcement Method (non-core):

Fillet center section

Second Leg Width:

4.2500 inches

First Leg Hole Diameter:

Between 0.6220 inches and 0.6330 inches

Second Leg Hole Diameter:

Between 0.5590 inches and 0.5700 inches

Second Leg Distance Between Hole Centers Along Width:

2.5000 inches

Second Leg Distance Between Hole Centers Along Length:

2.5000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.8750 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.9200 inches

First Leg Thickness:

0.2500 inches

Second Leg Thickness:

0.2500 inches

First Leg Width:

4.2500 inches

First Leg Distance Between Hole Centers Along Width:

2.5000 inches

First Leg Distance Between Hole Centers Along Length:

3.5000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.8750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.8120 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.25 radians

Material:

Steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020

Material Specification:

Astm-a569 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0