## NSN 5340-01-394-0434

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-394-0434

Manustina Hala Tuna
Mounting Hole Type:
Plain
First Leg Length:
73.0 millimeters
Second Leg Length:
25.0 millimeters
Second Leg Width:
26.0 millimeters
First Leg Hole Diameter:
Between 10.7 millimeters and 11.3 millimeters
Second Leg Distance From Edge To Hole Center Along Width:
13.0 millimeters
Second Leg Distance From Edge To Hole Center Along Length:
59.0 millimeters
Second Leg Slot Length:
Between 11.7 millimeters and 12.3 millimeters
Second Leg Slot Width:
Between 4.08 millimeters and 5.41 millimeters
First Leg Thickness:
0.1196 inches
Second Leg Thickness:
0.1196 inches
Center Section Height:
50.0 millimeters
Center Section Width:
26.0 millimeters
Center Section Thickness:
0.1196 inches
First Leg Width:
26.0 millimeters
First Leg Distance From Edge To Hole Center Along Width:
13.0 millimeters
First Leg Distance From Edge To Hole Center Along Length:
12.0 millimeters
First Leg Style:
Square
First Leg Hole Arrangement Style:
One hole
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
One slot

## NSN 5340-01-394-0434

Double Angle Bracket - Page 2 of 2



Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
3.0 radians
Second Leg Angle:
3.0 radians
Material:
Steel comp 1009
Material Specification:
Astm-a569 assn standard single material response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
N.I.
No
Fiig: