## NSN 5340-01-394-5380

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-394-5380

**Mounting Hole Type:** 

Plain

First Leg Length:

Between 63.0 millimeters and 67.0 millimeters

Second Leg Length:

Between 91.2 millimeters and 91.6 millimeters

Second Leg Width:

34.4 millimeters

First Leg Hole Diameter:

Between 25.3 millimeters and 25.5 millimeters

Second Leg Hole Diameter:

Between 7.0 millimeters and 7.3 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

15.2 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

35.5 millimeters

First Leg Thickness:

0.1196 inches

Second Leg Thickness:

0.1196 inches

First Leg Width:

Between 50.6 millimeters and 51.0 millimeters

First Leg Distance From Edge To Hole Center Along Width:

Between 24.3 millimeters and 25.5 millimeters

First Leg Distance From Edge To Hole Center Along Length:

26.0 millimeters

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

**Second Leg Hole Arrangement Style:** 

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 4.4 radians and 4.6 radians

Material:

Steel comp 1009

**Material Specification:** 

Astma-569 assn standard single material response

## NSN 5340-01-394-5380

Angle Bracket - Page 2 of 2



Surface Treatment:
Plastic polyurethane
Surface Treatment Specification:
Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-c-46168 spec.

Mil-std (military Standard):

A042a0