

View Online at <https://aerobasegroup.com/nsn/5340-01-394-5380>

Mounting Hole Type:

Plain

First Leg Length:

Between 63.0 millimeters and 67.0 millimeters

Second Leg Length:

Between 91.2 millimeters and 91.6 millimeters

Second Leg Width:

34.4 millimeters

First Leg Hole Diameter:

Between 25.3 millimeters and 25.5 millimeters

Second Leg Hole Diameter:

Between 7.0 millimeters and 7.3 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

15.2 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

35.5 millimeters

First Leg Thickness:

0.1196 inches

Second Leg Thickness:

0.1196 inches

First Leg Width:

Between 50.6 millimeters and 51.0 millimeters

First Leg Distance From Edge To Hole Center Along Width:

Between 24.3 millimeters and 25.5 millimeters

First Leg Distance From Edge To Hole Center Along Length:

26.0 millimeters

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 4.4 radians and 4.6 radians

Material:

Steel comp 1009

Material Specification:

Astma-569 assn standard single material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.