

View Online at <https://aerobasegroup.com/nsn/5340-01-395-1413>

Mounting Hole Type:

Plain

First Leg Length:

2.000 inches

Second Leg Length:

5.500 inches

Reinforcement Method (non-core):

Gusset both legs

Second Leg Width:

1.500 inches

First Leg Hole Diameter:

Between 0.311 inches and 0.336 inches

Second Leg Hole Diameter:

Between 0.311 inches and 0.336 inches

Second Leg Distance Between Hole Centers Along Length:

3.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.875 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

1.500 inches

First Leg Distance Between Hole Centers Along Width:

0.625 inches

First Leg Distance Between Hole Centers Along Length:

0.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.375 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 76.0 degrees and 86.0 degrees

Material:

Aluminum alloy 5083

Material Specification:

Qq-a-250/6 h321 or h323 federal specification single material response

Surface Treatment:

Paint

Surface Treatment Specification:

Mil-c-22750 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-22750 spec.