

View Online at <https://aerobasegroup.com/nsn/5340-01-397-1143>

Mounting Hole Type:

Countersunk

First Leg Length:

0.500 inches

Second Leg Length:

1.000 inches

End Application:

Pacer dawn

Second Leg Width:

0.400 inches

First Leg Hole Diameter:

0.138 inches

Second Leg Hole Diameter:

0.196 inches

Second Leg Distance Between Hole Centers Along Length:

0.400 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.200 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

0.400 inches

First Leg End Width:

0.100 inches

First Leg Distance From Edge To Hole Center Along Width:

0.200 inches

First Leg Distance From Edge To Hole Center Along Length:

0.180 inches

First Leg Style:

Square and tapered

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

Special Features:

Original name, bracket, adjusting

Material:

Steel comp 304

Material Specification:

Qq-s-763, cl304, cond a federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-std-171 military standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-std-171 spec.