

View Online at <https://aerobasegroup.com/nsn/5340-01-397-1143>

**Mounting Hole Type:**

Countersunk

**First Leg Length:**

0.500 inches

**Second Leg Length:**

1.000 inches

**End Application:**

Pacer dawn

**Second Leg Width:**

0.400 inches

**First Leg Hole Diameter:**

0.138 inches

**Second Leg Hole Diameter:**

0.196 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.400 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.200 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Thickness:**

0.090 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

0.400 inches

**First Leg End Width:**

0.100 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.200 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.180 inches

**First Leg Style:**

Square and tapered

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**Special Features:**

Original name, bracket, adjusting

**Material:**

Steel comp 304

**Material Specification:**

Qq-s-763, cl304, cond a federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-std-171 military standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-std-171 spec.