

View Online at <https://aerobasegroup.com/nsn/5340-01-397-8198>

Mounting Hole Type:

Plain

First Leg Length:

0.950 inches

Second Leg Length:

Between 1.437 inches and 1.563 inches

Second Leg Width:

0.880 inches

Second Leg End Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.440 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.625 inches

Second Leg Slot Length:

0.560 inches

Second Leg Slot Width:

Between 0.207 inches and 0.213 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

0.880 inches

First Leg End Width:

0.500 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

No hole

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Second Leg Slot Offset Angle:

15.0 degrees

Special Features:

Includes one stud , m63540/1-21c, located on first leg

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200/16 t6 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.