## NSN 5340-01-398-2378

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-398-2378

Mounting Hole Type:
Plain
First Leg Length:
0.750 inches
Second Leg Length:
1.250 inches
First Leg Hole Diameter:
Between 0.218 inches and 0.224 inches
Second Leg Hole Diameter:
Between 0.218 inches and 0.224 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
2.540 inches
Second Leg Distance Between Second And Third Hole Centers Along Width:
2.540 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.500 inches
First Leg Thickness:
0.060 inches
Second Leg Thickness:
0.060 inches
First Leg Width:
6.030 inches
First Leg End Width:
5.790 inches
First Leg Distance Between Hole Centers Along Width:
5.520 inches
First Leg Distance Between First And Second Hole Centers Along Width:
1.500 inches
First Leg Distance Between Second And Third Hole Centers Along Width:
2.500 inches
First Leg Distance From Edge To Hole Center Along Width:
0.250 inches
First Leg Distance From Edge To Hole Center Along Length:
0.380 inches
First Leg Style:
Chamfered ends
First Leg Hole Arrangement Style:
Four holes
Second Leg Style:
Chamfered ends
Second Leg Hole Arrangement Style:

Three holes

## **NSN 5340-01-398-2378** Angle Bracket - Page 2 of 2



Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
125.0 degrees
First Leg Chamfer Angle:
45.0 degrees
Second Leg Chamfer Angle:
45.0 degrees
Material:
Aluminum alloy 5052
Material Specification:
Qq-a-250/8 h32 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541 cl 3 military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-5541 spec.