

View Online at <https://aerobasegroup.com/nsn/5340-01-398-2378>

Mounting Hole Type:

Plain

First Leg Length:

0.750 inches

Second Leg Length:

1.250 inches

First Leg Hole Diameter:

Between 0.218 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.218 inches and 0.224 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

2.540 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

2.540 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.060 inches

Second Leg Thickness:

0.060 inches

First Leg Width:

6.030 inches

First Leg End Width:

5.790 inches

First Leg Distance Between Hole Centers Along Width:

5.520 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.500 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

2.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

125.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 h32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 cl 3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.