

View Online at <https://aerobasegroup.com/nsn/5340-01-406-1719>

First Leg Length:

2.000 inches

Second Leg Length:

1.830 inches

Second Leg Width:

0.250 inches

First Leg Slot Length:

0.500 inches

First Leg Slot Width:

0.281 inches

Second Leg Hole Diameter:

0.250 inches

Second Leg Distance Between Hole Centers Along Width:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.440 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

1.000 inches

First Leg Distance Between Hole Centers Along Length:

0.812 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Side radius

First Leg Hole Arrangement Style:

4 slots

Second Leg Style:

Side radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/8 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 ty3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.