NSN 5340-01-406-8043

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-406-8043

| g |
|--|
| Cross Sectional Shape: |
| Square or rectangular recess |
| Hole Diameter: |
| Between 0.251 inches and 0.258 inches |
| Width: |
| 8.120 inches |
| Flange Thickness: |
| 0.059 inches |
| Edge Shape: |
| Rectangle, four holes |
| Length: |
| 10.000 inches |
| Inside Width: |
| 6.500 inches |
| Inside Length: |
| 9.500 inches |
| Corner Radius: |
| 0.620 inches |
| Distance Between Holes Along Length: |
| 9.000 inches |
| Distance Between Holes Along Width: |
| 7.125 inches |
| Distance From First Hole Centerline To End Along Length: |
| 0.500 inches |
| Distance From First Hole Centerline To End Along Width: |
| 0.500 inches |
| First Recess Inside Height: |
| 1.430 inches |
| Inside Corner Radius: |
| 1.500 inches |
| Body Thickness: |
| 0.059 inches |
| Securing Device Type: |
| Special |
| Mounting Opening Shape Style: |
| Unthreaded hole |
| Material: |
| Steel |
| Material Specification: |
| Qq-s-698 federal specification single material response |
| Surface Treatment: |

Enamel semigloss

NSN 5340-01-406-8043

Access Cover - Page 2 of 2



Mil-e-15090 type 2 cl 2 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531c0

Mil-std (military Standard):

Mil-e-15090 spec.