

View Online at <https://aerobasegroup.com/nsn/5340-01-413-0824>

Mounting Hole Type:

Counterbored

First Leg Length:

1.6250 inches

Second Leg Length:

3.5550 inches

Second Leg Width:

Between 3.1000 inches and 3.1400 inches

First Leg Hole Diameter:

Between 0.4330 inches and 0.4440 inches

Second Leg Distance Between Hole Centers Along Width:

2.1300 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.4980 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.2500 inches

Second Leg Slot Length:

Between 0.3110 inches and 0.3220 inches

Second Leg Slot Width:

Between 0.1930 inches and 0.2010 inches

First Leg Thickness:

0.1250 inches

Second Leg Thickness:

0.1250 inches

First Leg Width:

Between 3.1000 inches and 3.1400 inches

First Leg Distance Between Hole Centers Along Width:

2.3000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.4380 inches

First Leg Distance From Edge To Hole Center Along Length:

0.5000 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.3500 radians and 0.4100 radians

Special Features:

The holes are counterbore

Material:

Aluminum alloy 5052

Material Specification:

Astm-b-209 assn standard single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.