

View Online at <https://aerobasegroup.com/nsn/5340-01-413-9812>

**First Leg Length:**

0.650 inches

**Second Leg Length:**

0.715 inches

**End Application:**

F-16 acft

**Second Leg Width:**

1.210 inches

**First Leg Slot Length:**

Between 0.581 inches and 0.591 inches

**First Leg Slot Width:**

0.308 inches

**Second Leg Hole Diameter:**

Between 0.161 inches and 0.171 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.910 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.148 inches

**First Leg Thickness:**

0.094 inches

**Second Leg Thickness:**

0.094 inches

**First Leg Width:**

1.210 inches

**First Leg End Width:**

1.198 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.605 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.271 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

Cut out

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

0.094 radians

**Second Leg Cutout Length:**

0.440 inches

**Second Leg Cutout Width:**

0.610 inches

**First Leg Chamfer Angle:**

45.0 degrees

**Special Features:**

2 holes either side of slot, 0.086-56 unc-2b; ends of second (cutout) leg are each rounded

**Material:**

Steel comp 304

**Material Specification:**

Qq-s-766 type 304, cond a federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, type vii (f-16, mthd 12) federal specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0