

View Online at <https://aerobasegroup.com/nsn/5340-01-413-9812>

First Leg Length:

0.650 inches

Second Leg Length:

0.715 inches

End Application:

F-16 acft

Second Leg Width:

1.210 inches

First Leg Slot Length:

Between 0.581 inches and 0.591 inches

First Leg Slot Width:

0.308 inches

Second Leg Hole Diameter:

Between 0.161 inches and 0.171 inches

Second Leg Distance Between Hole Centers Along Width:

0.910 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.148 inches

First Leg Thickness:

0.094 inches

Second Leg Thickness:

0.094 inches

First Leg Width:

1.210 inches

First Leg End Width:

1.198 inches

First Leg Distance From Edge To Hole Center Along Width:

0.605 inches

First Leg Distance From Edge To Hole Center Along Length:

0.271 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Cut out

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.094 radians

Second Leg Cutout Length:

0.440 inches

Second Leg Cutout Width:

0.610 inches

First Leg Chamfer Angle:

45.0 degrees

Special Features:

2 holes either side of slot, 0.086-56 unc-2b; ends of second (cutout) leg are each rounded

Material:

Steel comp 304

Material Specification:

Qq-s-766 type 304, cond a federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type vii (f-16, mthd 12) federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0