# NSN 5340-01-414-2188

Spacing Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-414-2188

## **Thread Class:**

2b left internal (includes through thread)

## **Thread Direction:**

Right-hand left internal (includes through thread)

## Thread Length:

0.1830 inches and 0.1930 inches left internal (includes through thread)

## Length:

0.1880 inches

## **Cross-sectional Shape:**

Hexagon

## Width Across Flats:

0.2500 inches

## Thready Qty Per Inch (tpi):

40 left internal (includes through thread)

## **Thread Size:**

0.1120 inches left internal (includes through thread)

## **Right Projection Diameter:**

Between 0.1850 inches and 0.1880 inches

## **Right Projection Length:**

Between 0.0720 inches and 0.0780 inches

# Material:

Copper alloy 360 standoff

## Material Specification:

Qq-b-626 federal specification single material response standoff

## Surface Treatment:

Tin standoff

# Surface Treatment Specification:

Mil-t-10727, type 1, type 2 military specification single treatment response standoff

## Style Designator:

Projection one end

# **Thread Series Designator:**

Unc left internal (includes through thread)

## Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A08900

# Mil-std (military Standard):

Mil-t-10727 spec.