

View Online at <https://aerobasegroup.com/nsn/5340-01-415-3422>

Mounting Hole Type:

Plain

First Leg Length:

2.2500 inches

Second Leg Length:

3.5000 inches

Reinforcement Method (non-core):

Rib stiffener center section

Second Leg Width:

2.0000 inches

First Leg Hole Diameter:

Between 0.4060 inches and 0.4600 inches

Second Leg Hole Diameter:

Between 0.2210 inches and 0.2580 inches

Second Leg Distance Between Hole Centers Along Length:

2.2500 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.0000 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.3750 inches

First Leg Thickness:

0.1900 inches

Second Leg Thickness:

0.1900 inches

Center Section Height:

3.2800 inches

Center Section Width:

2.000 inches

Center Section Thickness:

0.1900 inches

First Leg Width:

2.0000 inches

First Leg End Width:

1.2400 inches

First Leg Distance From Edge To Hole Center Along Width:

1.0000 inches

First Leg Distance From Edge To Hole Center Along Length:

0.7200 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.5700 radians

Second Leg Angle:

0.5700 radians

First Leg Chamfer Angle:

Between 40.0 degrees and 50.0 degrees

Material:

Aluminum alloy 5083

Material Specification:

Qq-a-250/6 federal specification single material response or qq-a-250/7 federal specification single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0