
NSN 5340-01-417-9837

Double Angle Bracket - Page 1 of 2





Mounting Hole Type:
Plain
First Leg Length:
1.0000 inches
Second Leg Length:
1.0000 inches
Second Leg Width:
15.0000 inches
First Leg Hole Diameter:
Between 0.4370 inches and 0.5000 inches
Second Leg Hole Diameter:
Between 0.4370 inches and 0.5000 inches
Second Leg Distance Between Hole Centers Along Width:
11.5000 inches
Second Leg Distance From Edge To Hole Center Along Width:
1.7500 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.5000 inches
First Leg Thickness:
0.1250 inches
Second Leg Thickness:
0.1250 inches
Center Section Height:
10.7500 inches
Center Section Width:
15.0000 inches
Center Section Thickness:
0.1250 inches
First Leg Width:
15.0000 inches
First Leg Corner Radius:
0.5000 inches
First Leg Style:
Corner radius
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical

NSN 5340-01-417-9837

Double Angle Bracket - Page 2 of 2



First Leg Angle:

60.0 degrees

Second Leg Angle:

0.3800 radians

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Qq-a-250/6 federal specification single material response or qq-a-250/7 federal specification single material response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0