

View Online at <https://aerobasegroup.com/nsn/5340-01-418-2009>

**Mounting Hole Type:**

Plain

**First Leg Length:**

Between 0.500 inches and 0.510 inches

**Second Leg Length:**

1.250 inches

**Second Leg Width:**

3.000 inches

**First Leg Hole Diameter:**

Between 0.210 inches and 0.220 inches

**Second Leg Hole Diameter:**

Between 0.250 inches and 0.254 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.310 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.350 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.315 inches

**First Leg Thickness:**

Between 0.080 inches and 0.090 inches

**Second Leg Thickness:**

Between 0.080 inches and 0.090 inches

**First Leg Width:**

3.000 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 1.345 inches and 1.355 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.160 inches and 0.165 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-200/8 t6 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 type 2 cl 1 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.