

View Online at <https://aerobasegroup.com/nsn/5340-01-418-2009>

Mounting Hole Type:

Plain

First Leg Length:

Between 0.500 inches and 0.510 inches

Second Leg Length:

1.250 inches

Second Leg Width:

3.000 inches

First Leg Hole Diameter:

Between 0.210 inches and 0.220 inches

Second Leg Hole Diameter:

Between 0.250 inches and 0.254 inches

Second Leg Distance Between Hole Centers Along Width:

2.310 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.350 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.315 inches

First Leg Thickness:

Between 0.080 inches and 0.090 inches

Second Leg Thickness:

Between 0.080 inches and 0.090 inches

First Leg Width:

3.000 inches

First Leg Distance Between Hole Centers Along Width:

Between 1.345 inches and 1.355 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.160 inches and 0.165 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200/8 t6 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 type 2 cl 1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.