

View Online at <https://aerobasegroup.com/nsn/5340-01-418-9106>

Mounting Hole Type:

Plain

First Leg Length:

1.490 inches

Second Leg Length:

2.400 inches

Reinforcement Method (non-core):

Beaded both legs

Second Leg Width:

0.800 inches

Second Leg Corner Radius:

0.120 inches

First Leg Hole Diameter:

0.098 inches

Second Leg Hole Diameter:

Between 0.246 inches and 0.252 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.400 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.400 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

First Leg Width:

0.800 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

0.380 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.190 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

0.220 inches

First Leg Distance From Edge To Hole Center Along Width:

0.210 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Distance Between First And Second Hole Centers Along Length:

0.190 inches

First Leg Distance Between Second And Third Hole Centers Along Length:

0.190 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5 t42 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 cl 1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.