

View Online at <https://aerobasegroup.com/nsn/5340-01-418-9761>

Mounting Hole Type:

Countersunk

First Leg Length:

Between 0.3700 inches and 0.4300 inches

Second Leg Length:

Between 1.2200 inches and 1.2800 inches

Second Leg Width:

Between 2.5900 inches and 2.6500 inches

First Leg Hole Diameter:

Between 0.1400 inches and 0.1460 inches

Second Leg Hole Diameter:

0.2700 inches

Second Leg Distance Between Hole Centers Along Width:

2.2500 inches

Second Leg Distance Between Hole Centers Along Length:

0.3120 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.1900 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.2200 inches

First Leg Thickness:

0.6200 inches

Second Leg Thickness:

0.0620 inches

First Leg Width:

Between 0.1990 inches and 2.0300 inches

First Leg Distance Between Hole Centers Along Width:

1.5000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.2500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.1500 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.09 radians

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.