

View Online at <https://aerobasegroup.com/nsn/5340-01-418-9761>

**Mounting Hole Type:**

Countersunk

**First Leg Length:**

Between 0.3700 inches and 0.4300 inches

**Second Leg Length:**

Between 1.2200 inches and 1.2800 inches

**Second Leg Width:**

Between 2.5900 inches and 2.6500 inches

**First Leg Hole Diameter:**

Between 0.1400 inches and 0.1460 inches

**Second Leg Hole Diameter:**

0.2700 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.2500 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.3120 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.1900 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.2200 inches

**First Leg Thickness:**

0.6200 inches

**Second Leg Thickness:**

0.0620 inches

**First Leg Width:**

Between 0.1990 inches and 2.0300 inches

**First Leg Distance Between Hole Centers Along Width:**

1.5000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.2500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.1500 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

0.09 radians

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.