## NSN 5340-01-422-6066

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-422-6066

Mounting Hole Type:
Plain
First Leg Length:
0.912 inches
Second Leg Length:
1.120 inches
Second Leg Width:
10.000 inches
Second Leg Corner Radius:
0.250 inches
Second Leg Hole Diameter:
Between 0.290 inches and 0.293 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
4.500 inches
Second Leg Distance Between Second And Third Hole Centers Along Width:
4.500 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.500 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.500 inches
First Leg Thickness:
0.062 inches
Second Leg Thickness:
0.062 inches
Center Section Height:
1.072 inches
Center Section Width:
10.000 inches
Center Section Thickness:
0.062 inches
First Leg Width:
10.000 inches
First Leg Corner Radius:
0.250 inches
First Leg Style:
Corner radius
First Leg Hole Arrangement Style:
No hole
Second Leg Style:
Corner radius

Three holes

**Second Leg Hole Arrangement Style:** 

## NSN 5340-01-422-6066

Double Angle Bracket - Page 2 of 2



Features Provided:
Nut and mounting pad
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Material:
Aluminum alloy 5052
Material Specification:
Qq-a-250/8 h32 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541 cl 1a military specification single treatment response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-5541 spec.