

View Online at <https://aerobasegroup.com/nsn/5340-01-423-9631>

**Mounting Hole Type:**

Threaded

**First Leg Length:**

0.700 inches

**Second Leg Length:**

0.750 inches

**End Application:**

Pacer dawn

**Second Leg Width:**

0.250 inches

**First Leg Hole Diameter:**

0.112 inches

**Second Leg Hole Diameter:**

0.112 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.125 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.137 inches

**First Leg Thickness:**

0.188 inches

**Second Leg Thickness:**

0.188 inches

**First Leg Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.125 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.187 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Bracket contains 3 threaded holes, 4-40unc-2b thru, 100.0 degree countersink to 0.150 in diameter (both sides)

**Material:**

Aluminum alloy 6061

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, class 3 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.