NSN 5340-01-424-1165

Spacing Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-424-1165 **Thread Class:** 2b left internal (includes through thread) **Thread Direction:** Right-hand right external Thread Length: 0.1200 inches left internal (includes through thread) Flange Thickness: Between 0.1730 inches and 0.2030 inches Flange Width Across Flats: Between 0.1730 inches and 0.2030 inches **Cross-sectional Shape:** Hexagon Width Across Flats: Between 0.1730 inches and 0.2030 inches Thready Qty Per Inch (tpi): 56 left internal (includes through thread) **Thread Size:** 0.1120 inches right internal **Right Projection Diameter:** Between 0.1061 inches and 0.1112 inches **Right Projection Length:** Between 0.2970 inches and 0.3270 inches Material: Steel comp 303 standoff **Material Specification:** Astm-a-582 assn standard single material response standoff **Surface Treatment:** Passivate standoff **Surface Treatment Specification:** Mil-s-5002 military specification single treatment response standoff **Thread Series Designator:** Unc right external Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A08900

Mil-std (military Standard):

Mil-s-5002 spec.