

View Online at <https://aerobasegroup.com/nsn/5340-01-424-6251>

First Leg Length:

1.1000 inches

Second Leg Length:

1.7500 inches

Second Leg Width:

6.7500 inches

First Leg Hole Diameter:

0.0140 inches

Second Leg Distance Between Hole Centers Along Width:

3.7500 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.5000 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.6250 inches

Second Leg Slot Length:

0.6250 inches

Second Leg Slot Width:

Between 0.2400 inches and 0.2600 inches

First Leg Thickness:

0.0900 inches

Second Leg Thickness:

0.0900 inches

First Leg Width:

6.7500 inches

First Leg Distance Between First And Second Hole Centers Along Width:

2.7500 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

2.7500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.6250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.3500 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.1900 radians

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.