## NSN 5340-01-425-5393

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-425-5393

2.0000 inches

Second Leg Length:

6.7500 inches

## Second Leg Width:

5.0000 inches

First Leg Slot Length:

0.4370 inches

First Leg Slot Width:

0.4370 inches

### Second Leg Distance Between Hole Centers Along Width:

#### 3.0000 inches

Second Leg Distance From Edge To Hole Center Along Width:

#### 1.0000 inches

Second Leg Distance From Edge To Hole Center Along Length:

#### 1.1250 inches

Second Leg Slot Length:

1.0000 inches

Second Leg Slot Width:

0.3750 inches

#### First Leg Thickness:

0.1250 inches

#### Second Leg Thickness:

0.1250 inches

#### First Leg Width:

5.0000 inches

## First Leg Distance Between Hole Centers Along Width:

3.0000 inches

## First Leg Distance From Edge To Hole Center Along Width:

1.0000 inches

## First Leg Distance From Edge To Hole Center Along Length:

0.9390 inches

#### First Leg Style:

Square

## First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

## Second Leg Hole Arrangement Style:

2 slots

## Second Leg Relationship To First Leg:

Not identical

# NSN 5340-01-425-5393

Angle Bracket - Page 2 of 2



### First Leg Angle:

0.1200 radians

#### Material:

Aluminum alloy 5052

## Material Specification:

Qq-a-250/8 federal specification single material response

### Surface Treatment:

Anodize

## Surface Treatment Specification:

Mil-f-14072 military specification single treatment response

#### Style Designator:

Angle

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A042a0

#### Mil-std (military Standard):

Mil-f-14072 spec.