NSN 5340-01-425-5570

Corner Brace - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-425-5570 **Material Thickness:**

1.0000 inches

First Leg Length:

8.0000 inches

Second Leg Length:

10.1600 inches

Second Leg Width:

10.1600 inches

First Leg Slot Length:

Between 0.6000 inches and 0.6400 inches

First Leg Slot Width:

Between 0.3600 inches and 0.4000 inches

Second Leg Distance Between Hole Centers Along Width:

3.0000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.4420 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.5580 inches

Second Leg Slot Length:

Between 0.6000 inches and 0.6400 inches

Second Leg Slot Width:

Between 0.3600 inches and 0.4000 inches

First Leg Width:

8.0000 inches

First Leg Distance Between Hole Centers Along Width:

3.0000 inches

First Leg Distance From Edge To Hole Center Along Width:

4.0000 inches

First Leg Distance From Edge To Hole Center Along Length:

0.4420 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Angle:

0.1300 radians

Second Leg Relationship To First Leg:

Not identical

NSN 5340-01-425-5570

Corner Brace - Page 2 of 2

Fiig: A042a0



Material:
Aluminum alloy 5052
Material Specification:
Qq-a-250/8 federal specification single material response
Style Designator:
Triangle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No