

View Online at <https://aerobasegroup.com/nsn/5340-01-425-8621>

**Mounting Hole Type:**

Plain

**First Leg Length:**

Between 0.8300 inches and 0.8500 inches

**Second Leg Length:**

1.5400 inches

**Second Leg Width:**

Between 1.2400 inches and 1.2600 inches

**First Leg Slot Length:**

Between 0.3900 inches and 0.4100 inches

**First Leg Slot Width:**

Between 0.210 inches and 0.230 inches

**Second Leg Hole Diameter:**

Between 0.3050 inches and 0.3150 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.5000 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.2200 inches and 0.2400 inches

**First Leg Thickness:**

Between 0.0850 inches and 0.0950 inches

**Second Leg Thickness:**

Between 0.0850 inches and 0.0950 inches

**First Leg Width:**

Between 1.2400 inches and 1.2600 inches

**First Leg Corner Radius:**

Between 0.1100 inches and 0.1300 inches

**First Leg Distance Between Hole Centers Along Width:**

0.6500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.3000 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.3800 inches

**Second Leg End Radius:**

Between 0.2200 inches and 0.2400 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

End radius and tapered

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

Between 0.26 radians and 0.28 radians

**Material:**

Nickel alloy 625

**Material Specification:**

Ams5599 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A042a0