

View Online at <https://aerobasegroup.com/nsn/5340-01-426-8886>

**Center To Center Distance Between Bolt Holes Along Width:**

2.625 inches

**Center To Center Distance Between Bolt Holes Along Length:**

3.625 inches

**Wheel Quantity:**

1

**Safe Operating Load Rating:**

400.0 pounds

**Material And Location:**

Steel plate err-100 err-100

**Surface Treatment And Location:**

Cadmium body or zinc plated body or painted body or lacquer body or enamel body

**Wheel Type:**

Built up

**Wheel Diameter:**

6.000 inches

**Effective Height:**

7.375 inches

**Features Provided:**

Swivel lubrication fitting

**Plate Style:**

Rectangular

**Wheel Bearing Type:**

Roller or ball

**Swivel Bearing Type:**

Annular ball

**Swivel Bearing Arrangement:**

Two row or two level

**Tread Width:**

2.000 inches

**Caster Plate Length:**

5.500 inches

**Caster Plate Width:**

5.000 inches

**Caster Plate Mounting Hole Diameter:**

0.375 inches

**Special Features:**

No surface finish on aluminum casters; optional height 8.000 in.; optional mounting plate hole spacing 3.000 in. By 3.000 in.

**Style Designator:**

Swivel offset

**Specification Or Standard:**

A group and 2 type and 4 class and 5 style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A25600