

View Online at <https://aerobasegroup.com/nsn/5340-01-429-8501>

Mounting Hole Type:

Plain

First Leg Length:

1.250 inches

Second Leg Length:

3.000 inches

Second Leg Width:

11.500 inches

First Leg Hole Diameter:

Between 0.745 inches and 0.755 inches

Second Leg Hole Diameter:

Between 0.318 inches and 0.344 inches

Second Leg Distance Between Hole Centers Along Width:

3.000 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

3.000 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

4.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

2.218 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

11.500 inches

First Leg Distance Between First And Second Hole Centers Along Width:

5.000 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

5.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.375 inches

Second Leg Side Radius:

0.120 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Side radius

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.310 radians

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Qq-a-200/4 federal specification 1st material response or qq-a-200/5 federal specification 2nd material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mi-c-5541, class 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

spec.