

View Online at <https://aerobasegroup.com/nsn/5340-01-430-3838>

**First Leg Length:**

0.460 inches

**Second Leg Length:**

2.420 inches

**Second Leg Width:**

0.620 inches

**First Leg Hole Diameter:**

Between 0.155 inches and 0.161 inches

**First Leg Thickness:**

0.040 inches

**Second Leg Thickness:**

0.040 inches

**Center Section Height:**

1.030 inches

**Center Section Width:**

0.620 inches

**Center Section Thickness:**

0.040 inches

**First Leg Width:**

0.620 inches

**First Leg End Width:**

0.420 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.310 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.280 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Extended hook

**Second Leg Hole Arrangement Style:**

No hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

0.060 radians

**Second Leg Angle:**

0.060 radians

**First Leg Chamfer Angle:**

45.0 degrees

**Special Features:**

Uassembly includes; reinforcement plate along second leg length dimensions, 2.050 inch in length, .620 inch in width; insulated sleeve p/n-m23053/5-109-0; solid countersunk rivet p/n-ms20426ad2-3; self-locking plate nut p/n-nas1068rx06

**Material:**

Steel comp 302

**Material Specification:**

Qq-s-766, cl302, cond a federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Astm a380 assn standard single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0