

View Online at <https://aerobasegroup.com/nsn/5340-01-430-3838>

First Leg Length:

0.460 inches

Second Leg Length:

2.420 inches

Second Leg Width:

0.620 inches

First Leg Hole Diameter:

Between 0.155 inches and 0.161 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

Center Section Height:

1.030 inches

Center Section Width:

0.620 inches

Center Section Thickness:

0.040 inches

First Leg Width:

0.620 inches

First Leg End Width:

0.420 inches

First Leg Distance From Edge To Hole Center Along Width:

0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

0.280 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Extended hook

Second Leg Hole Arrangement Style:

No hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.060 radians

Second Leg Angle:

0.060 radians

First Leg Chamfer Angle:

45.0 degrees

Special Features:

Uassembly includes; reinforcement plate along second leg length dimensions, 2.050 inch in length, .620 inch in width; insulated sleeve p/n-m23053/5-109-0; solid countersunk rivet p/n-ms20426ad2-3; self-locking plate nut p/n-nas1068rx06

Material:

Steel comp 302

Material Specification:

Qq-s-766, cl302, cond a federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Astm a380 assn standard single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0