

View Online at <https://aerobasegroup.com/nsn/5340-01-431-1407>

Mounting Hole Type:

Plain

First Leg Length:

2.380 inches

Second Leg Length:

4.500 inches

Reinforcement Method (non-core):

Gusset both legs

Second Leg Width:

0.620 inches

First Leg Hole Diameter:

0.219 inches

Second Leg Hole Diameter:

0.156 inches

Second Leg Distance Between Hole Centers Along Length:

3.300 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.380 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.059 inches

Second Leg Thickness:

0.059 inches

First Leg Width:

0.620 inches

First Leg Distance Between Hole Centers Along Length:

1.620 inches

First Leg Distance From Edge To Hole Center Along Width:

0.380 inches

First Leg Distance From Edge To Hole Center Along Length:

0.260 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Opposite of p/n 930-11843-3, cagec 04801

Material:

Steel comp 1009

Material Specification:

Astm a366 assn standard single material response

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-e-15090 type 3 cl 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-e-15090 spec.