

View Online at <https://aerobasegroup.com/nsn/5340-01-432-0498>

Mounting Hole Type:

Plain

First Leg Length:

Between 2.2200 inches and 2.2500 inches

Second Leg Length:

Between 6.7200 inches and 6.7500 inches

Second Leg Width:

Between 9.9700 inches and 10.0000 inches

Second Leg Corner Radius:

Between 0.3000 inches and 0.3200 inches

First Leg Slot Length:

Between 1.0000 inches and 1.2000 inches

First Leg Slot Width:

Between 0.4000 inches and 0.6000 inches

Second Leg Hole Diameter:

Between 0.2500 inches and 0.2700 inches

Second Leg Distance Between Upper Hole Centers Along Width:

Between 5.8600 inches and 5.8800 inches

Second Leg Distance Between Lower Hole Centers Along Width:

Between 4.2400 inches and 4.2600 inches

Second Leg Distance Between Hole Centers Along Length:

3.2400 mils and 3.2600 centimeters

Second Leg Distance Between First And Second Hole Centers Along Width:

0.8100 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.4900 inches and 0.5100 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 1.4900 inches and 1.5100 inches

First Leg Thickness:

0.1900 inches

Second Leg Thickness:

0.1900 inches

First Leg Width:

Between 9.9700 inches and 10.0000 inches

First Leg Corner Radius:

Between 0.3000 inches and 0.3200 inches

First Leg Distance Between Hole Centers Along Width:

Between 6.4800 inches and 6.5200 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 1.7300 inches and 1.7700 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.9800 inches and 1.0200 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.1880 radians and 0.1900 radians

Special Features:

This is opposite of part number 11b252003- (left hand)

Material:

Aluminum alloy 5052

Material Specification:

Astm-b-209 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-srd-171, finish 7.3.1 military standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-srd-171 spec.