NSN 5340-01-432-0507

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-432-0507

Mounting Hole Type:

Plain

First Leg Length:

Between 2.2200 inches and 2.2500 inches

Second Leg Length:

Between 6.7200 inches and 6.7500 inches

Second Leg Width:

Between 9.9700 inches and 10.0000 inches

Second Leg Corner Radius:

Between 0.3000 inches and 0.3200 inches

First Leg Hole Diameter:

Between 0.2500 inches and 0.2700 inches

Second Leg Distance Between Hole Centers Along Width:

Between 6.4800 inches and 6.5200 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 1.7300 inches and 1.7700 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.9800 inches and 1.0200 inches

Second Leg Slot Length:

Between 1.0000 inches and 1.2000 inches

Second Leg Slot Width:

Between 0.4000 inches and 0.6000 inches

First Leg Thickness:

0.1900 inches

Second Leg Thickness:

0.1900 inches

First Leg Width:

Between 9.9700 inches and 10.0000 inches

First Leg Corner Radius:

Between 0.3000 inches and 0.3200 inches

First Leg Distance Between Upper Hole Centers Along Width:

Between 5.8600 inches and 5.8800 inches

First Leg Distance Between Lower Hole Centers Along Width:

Between 4.2400 inches and 4.2600 inches

First Leg Distance Between Hole Centers Along Length:

Between 3.2400 inches and 3.2600 inches

First Leg Distance Between First And Second Hole Centers Along Width:

Between 1.3700 inches and 1.3900 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.4900 inches and 0.5100 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 1.4900 inches and 1.5100 inches

NSN 5340-01-432-0507 Angle Bracket - Page 2 of 2



First Leg Style:
Corner radius
First Leg Hole Arrangement Style:
Four holes
Second Leg Style:
Corner radius
Second Leg Hole Arrangement Style:
2 slots
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
Between 0.1880 radians and 0.1920 radians
Material:
Aluminum alloy 5052
Material Specification:
Astm-b-209 assn standard single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-std-171, finish 7.3.1 military standard single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-std-171 spec.