

View Online at <https://aerobasegroup.com/nsn/5340-01-432-6197>

**Mounting Hole Type:**

Plain

**First Leg Length:**

Between 3.0900 inches and 3.1500 inches

**Second Leg Length:**

Between 11.4700 inches and 11.5300 inches

**Second Leg Width:**

Between 6.2200 inches and 6.2800 inches

**First Leg Hole Diameter:**

Between 0.4060 inches and 0.4160 inches

**Second Leg Hole Diameter:**

Between 0.2500 inches and 0.2600 inches

**Second Leg Distance Between Upper Hole Centers Along Width:**

4.0000 inches

**Second Leg Distance Between Hole Centers Along Length:**

8.0000 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

2.0000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.1100 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

1.5300 inches

**First Leg Thickness:**

0.1250 inches

**Second Leg Thickness:**

0.1250 inches

**First Leg Width:**

Between 6.2200 inches and 6.2800 inches

**First Leg Distance Between Hole Centers Along Width:**

5.0000 inches

**First Leg Distance Between Hole Centers Along Length:**

Between 1.0900 inches and 1.1500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.5900 inches and 0.6500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.4700 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Four holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**Special Features:**

There is a piece attached to the bracket.

**Material:**

Aluminum alloy 5052

**Material Specification:**

Astm-b-209 assn standard single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-std-171, finish 7.3.1 military standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-std-171 spec.