

View Online at <https://aerobasegroup.com/nsn/5340-01-432-6197>

Mounting Hole Type:

Plain

First Leg Length:

Between 3.0900 inches and 3.1500 inches

Second Leg Length:

Between 11.4700 inches and 11.5300 inches

Second Leg Width:

Between 6.2200 inches and 6.2800 inches

First Leg Hole Diameter:

Between 0.4060 inches and 0.4160 inches

Second Leg Hole Diameter:

Between 0.2500 inches and 0.2600 inches

Second Leg Distance Between Upper Hole Centers Along Width:

4.0000 inches

Second Leg Distance Between Hole Centers Along Length:

8.0000 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

2.0000 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.1100 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.5300 inches

First Leg Thickness:

0.1250 inches

Second Leg Thickness:

0.1250 inches

First Leg Width:

Between 6.2200 inches and 6.2800 inches

First Leg Distance Between Hole Centers Along Width:

5.0000 inches

First Leg Distance Between Hole Centers Along Length:

Between 1.0900 inches and 1.1500 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.5900 inches and 0.6500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.4700 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

Special Features:

There is a piece attached to the bracket.

Material:

Aluminum alloy 5052

Material Specification:

Astm-b-209 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-std-171, finish 7.3.1 military standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-std-171 spec.