NSN 5340-01-433-1944

Rigid Caster - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-433-1944

| Wheel Quantity: |
|---|
| 1 |
| Safe Operating Load Rating: |
| 670.0 pounds |
| Material And Location: |
| Rubber tire |
| Wheel Type: |
| Solid |
| Wheel Diameter: |
| 3.0000 inches |
| Effective Height: |
| 10.5000 inches |
| Plate Style: |
| Rectangular |
| Tread Width: |
| 2.5000 inches |
| Caster Plate Length: |
| 5.9000 inches |
| Caster Plate Width: |
| Between 5.2000 inches and 6.2000 inches |
| Center To Center Major Distance Between Mounting Slots Along Length: |
| 5.1250 inches |
| Center To Center Minor Distance Between Mounting Slots Along Length: |
| 5.22500 inches |
| Center To Center Major Distance Between Mounting Slots Along Width: |
| 4.1250 inches |
| Center To Center Minor Distance Between Mounting Slots Along Width: |
| 3.3750 inches |
| Caster Plate Mounting Slot Length: |
| 0.5630 inches |
| Caster Plate Mounting Slot Width: |
| 0.5630 inches |
| Special Features: |
| The mounting plate and horn assemlby shall be made of steel or aluminum |
| Style Designator: |
| Rigid |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| |

No

NSN 5340-01-433-1944 Rigid Caster - Page 2 of 2



Fiig:

A25600