

View Online at <https://aerobasegroup.com/nsn/5340-01-433-2066>

Wheel Quantity:

1

Safe Operating Load Rating:

2000.0 pounds

Material And Location:

Plastic, phenolic tire

Wheel Type:

Solid

Wheel Diameter:

6.0000 inches

Effective Height:

7.5000 inches

Plate Style:

Rectangular

Swivel Bearing Type:

Ball

Swivel Bearing Arrangement:

Two row

Tread Width:

2.5000 inches

Caster Plate Length:

Between 6.9000 inches and 7.5000 inches

Caster Plate Width:

Between 5.2000 inches and 6.2000 inches

Center To Center Major Distance Between Mounting Slots Along Length:

6.1250 inches

Center To Center Minor Distance Between Mounting Slots Along Length:

5.2500 inches

Center To Center Major Distance Between Mounting Slots Along Width:

4.1250 inches

Center To Center Minor Distance Between Mounting Slots Along Width:

3.3750 inches

Caster Plate Mounting Slot Width:

0.5630 inches

Special Features:

The plate mounting and horn assembly shall be made of steel or aluminum; the axle is made of steel and secured by locknut; there is a brake and swivel lock attached to the caster

Style Designator:

Swivel offset

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A25600