

View Online at <https://aerobasegroup.com/nsn/5340-01-436-1654>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.7220 inches

**Second Leg Length:**

1.0000 inches

**Second Leg Width:**

5.0200 inches

**First Leg Hole Diameter:**

Between 0.2120 inches and 0.2180 inches

**Second Leg Hole Diameter:**

Between 0.2200 inches and 0.2260 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

Between 2.2150 inches and 2.2250 inches

**Second Leg Distance Between Second And Third Hole Centers Along Width:**

Between 2.2150 inches and 2.2250 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.2900 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.3950 inches

**First Leg Thickness:**

0.2500 inches

**Second Leg Thickness:**

0.0970 inches

**First Leg Width:**

5.0200 inches

**First Leg End Width:**

3.3330 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 2.8280 inches and 3.8380 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.7920 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.2500 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

0.1500 radians

**First Leg Chamfer Angle:**

0.12 radians

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-200/16 federal specification single material response or qq-a-200/8 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 3, cl2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.