

View Online at <https://aerobasegroup.com/nsn/5340-01-436-1654>

Mounting Hole Type:

Plain

First Leg Length:

0.7220 inches

Second Leg Length:

1.0000 inches

Second Leg Width:

5.0200 inches

First Leg Hole Diameter:

Between 0.2120 inches and 0.2180 inches

Second Leg Hole Diameter:

Between 0.2200 inches and 0.2260 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

Between 2.2150 inches and 2.2250 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

Between 2.2150 inches and 2.2250 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.2900 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.3950 inches

First Leg Thickness:

0.2500 inches

Second Leg Thickness:

0.0970 inches

First Leg Width:

5.0200 inches

First Leg End Width:

3.3330 inches

First Leg Distance Between Hole Centers Along Width:

Between 2.8280 inches and 3.8380 inches

First Leg Distance From Edge To Hole Center Along Width:

0.7920 inches

First Leg Distance From Edge To Hole Center Along Length:

0.2500 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.1500 radians

First Leg Chamfer Angle:

0.12 radians

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200/16 federal specification single material response or qq-a-200/8 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 3, cl2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.